

Instructions manual

Honey tank transport trolley.
For tank diameters: 400, 500 and 600mm.



Przedsiębiorstwo Pszczelarskie Tomasz Łyson

Spółka z o.o. Spółka Komandytowa

34-125 Sułkowice, ul. Raclawicka 162, Polska

www.lyson.com.pl, email; lyson@lyson.com.pl

tel. 33/875-99-40, 33/870-64-02

Headquarters: Klecza Dolna 148, 34-124 Klecza Górna

Table of contents

This manual covers following devices (codes): W6601, W6602, W6603

1. General safety rules
 - 1.1. Intended use
 - 1.2. Operation safety
2. Preparations before assembly.
 - 2.1. Assembly instructions
3. Product description
 - 3.1. Technical specifications
4. Storage
5. Maintenance and cleaning
6. Waste disposal and environmental protection
7. Warranty



1. General safety instructions

Before first use read the manual carefully and follow the instructions contained therein. The manufacturer is not liable for damage caused by equipment used inappropriately or by incorrect handling.

1.1. Intended use

1. The trolley is designed for easy transport of honey tanks.
2. Use the trolley on level, smooth surfaces.



1.2. Operation safety

- a) Always lock caster wheel brakes after moving.
- b) Avoid any rough surfaces when moving to avoid damaging the wheels or tipping the trolley and the tank.
- c) The device is not intended for use by persons (including children) with limited physical, sensory or mental abilities, or by inexperienced users, unless under supervision or with instructions given by an accountable party. This device is not a toy, and shouldn't be used as one. Children should not to play with it.

2. Preparations before assembly.

Before assembling the trolley, check the number of components according to the list in section 3. 3. Prepare a Phillips screwdriver, spanner 7 and two spanners 17 (one of them ring or socket style).

2.1. Assembly instructions

Assembly:

Begin assembly by sorting out elements 1 and 8.

- slide elements 1 onto elements 8 (see the diagram),
- insert the screws 9 from the top into the assembled sides' mounting holes,
- put the washers 6 and nuts 7 onto the screws (do not tighten),
- insert the screws 3 into the wheel mounting holes from the bottom and slide them in the dedicated holes in the frame,
- put the washers 4 and nuts 5 onto the screws and tighten them down using two spanners 17,
- tighten down screws 9 using the Phillips screwdriver and the spanner 7.

3. Product description

Fig. 1 elements:

- | | | |
|----|-------------------------------------|---------|
| 1. | side element I - outer | - 2 pcs |
| 2. | caster wheel w/ brake 50mm diameter | - 4 pcs |
| 3. | Hex screw M10x35 | - 2 pcs |
| 4. | spring washer 10,2 | - 4 pcs |
| 5. | nut M10 | - 4 pcs |
| 6. | washer 4 | - 8 pcs |
| 7. | hex nut M4 | - 8 pcs |
| 8. | side element II- inner | - 2 pcs |
| 9. | tapered head screw M4x10 | - 8 pcs |

3.1. Technical specifications:

Made of 2 mm thick 0H18N9 acid resistant stainless-steel.

W6601 – dedicated for tank diameter of 400 mm
- dimensions: 140 x 320 x 320 mm
- weight: 4,5 KG
- max load: 100 KG

W6602 – dedicated for tank diameter of 500 mm
- dimensions: 160 x 420 x 420 mm
- weight: 6 KG
- max load: 280 KG

W6603 – dedicated for tank diameter of 600 mm
- dimensions : 160 x 520 x 520 mm
- weight: 7,5 KG
- max load: 280 KG

4. Storage

Clean and dry the unit thoroughly after use. Store the device in a dry room.

An additional technical check should be carried out periodically, and if any defects are found, please contact the manufacturer.

5. Cleaning and maintenance



Clean with hot water and a soft cloth using detergents allowed in food industry.

No parts of the device require any additional protection.

6. Waste disposal and environmental protection

The used product must be disposed in accordance with the local regulations. Return the device to a collection point from where it can be submitted for environmentally compatible recycling.

The consumer has the right to return used equipment directly to the manufacturer's distribution network, free of charge, while replacing it with a new unit as long as the used device is of the same kind and same application as the newly purchased device.

7. Warranty

The product purchased from the Lyson Company is covered by a manufacturer's warranty. The warranty period is 24 months from the date of purchase.

All purchased products come with receipts or VAT invoices.

Warranty details at:

www.lyson.com.pl

Fig. 1

