INSTRUCTIONS MANUAL

Heated lid for honey settling tanks 100÷150L.*





Przedsiębiorstwo Pszczelarskie Łysoń

Spółka z o.o. 34-124 Klecza Górna, st.Pszczela 2, Poland www.lyson.eu, e-mail; lyson@lyson.com.pl Tel. +48 33/875-99-40, +48 33/870-64-02

Instructions Manual of heated lid for honey settling tanks *(settling tak is bought separately)

Product code: W5010

WARNING!

Before first use read the manual carefully and follow the instructions contained therein. The manufacturer is not liable for damage caused by equipment used inappropriately or by incorrect handling.

For indoor use only

Operation safety

- The device must not be operated by persons under the age of eighteen or by persons with limited physical, sensory or mental abilities or lacking in knowledge and experience.
- Do not allow children to play with the appliance.
- Children and pets should not get close to a running or cooling appliance. Easily accessible parts get very hot.
- Do not allow children near the working appliance
- Do not leave the appliance unattended during operation.
- Do not place any objects on the lid while the appliance is running.
- Improper use can cause dangerous accidents.
- Do not use abrasive agents, sharp tools, metal washers or agents not designed for cleaning equipment which is in contact with food to clean the appliance.
- Before using the appliance, unpack it, clean it thoroughly using a mild detergent suitable for cleaning food equipment and rinse it thoroughly with clean water.

(for more information on cleaning agents see www.lyson.com.pl)

- Do not clean the appliance while it is still plugged in!
- Before starting the washing process, the mains plug must be pulled out.
- Do not move the appliance during operation as burns, knocking over or damage to the appliance may occur.
- When working with the appliance, protective clothing is required to protect the body from burns, as the lid
- required to protect the body from burns, as the lid heats up during operation.
- It is forbidden to remove the cover while the appliance is in operation, as the escaping steam may burn the user.
- Lift the lid once it has cooled down using protective gloves.



Never carry out any repairs during operation



Do not remove covers during operation



Electrical safety

- Make sure that the nominal voltage of the device and power source are compatible.
- The electrical supply system must be fitted with a residual-current circuit breaker with rated tripping current not higher than 30mA. Performance of the circuit breaker should be checked periodically.
- eriodically check the condition of the power cord. Replace the power cord if damaged. Replacing the power cord can only be performed by the manufacturer or by qualified personnel.
- Do not use the device if the power cord is damaged!
- In the event of damage to the device, to avoid any health and safety risks, repairs should be carried out only by qualified personnel.
- Do not pull the power cord.
- Keep the power cord away from heat sources and sharp edges to ensure its good condition.

IMPORTANT!

<u>Unplug the device before commencing any</u> maintenance or cleaning procedures and make sure it is completely cool!

The appliance is washed with hot water and detergent (approved for use in the food industry) using a soft flannel cloth, taking care to protect the electrical components. After washing, rinse thoroughly with clean water and dry. Store the appliance in a dry room.

Do not treat any parts of the unit with chemicals.i.



Operation instructions

- 1. Fill the basket with cappings, cut combs from the frames, and place in a settling tank placed on a stand (not included) with the drain valve open and the wax container (not included) in place.
- 2. Place the lid on the settling tank.
 - The lid must not be plugged in during application and the temperature controller is set to the "0" position.
- 3. Once the lid has been placed on the settling tank, plug it in and set the controller to the appropriate temperature.
 - the melting time depends on the quality of the cappings (temperature, batch compaction).

- 4. Once the melting process is complete, turn the regulator to the "0" position and unplug from the mains!!!
- 5. We wait until the lid has cooled down.
- 6. Empty the basket of residue and fill it with a new load of wax.



HOT SURFACE AND CONTENTS

Special care must be taken when working with the lid so that burns do not occur. It is forbidden for children to be in the room where the melting process takes place.

Temperature controller Heater operation Indicator light Indicator light Image: state of the s

Technical parameters

- power supply 230V

with thermostat

- temperature range 30-120°C
- heater power: 2kW
- acid-resistant stainless steel

Waste disposal and environmental protection

The used product must be disposed in accordance with the local regulations. Return the device to a collection point from where it can be submitted for environmentally compatible recycling.

The consumer has the right to return used equipment directly to the manufacturer's distribution network, free of charge, while replacing it with a new unit as long as the used device is of the same kind and same application as the newly purchased device.

Warranty

The product purchased from the Lyson Company is covered by a manufacturer's warranty. The warranty period is 24 months from the date of purchase.

All purchased products come with receipts or VAT invoices. Warranty details at:

www.lyson.com.pl

*ZThe product photos are illustrations and may occasionally differ from the actual appearance of the product. However, this does not alter its basic characteristics.